

TECHNICAL SPECIFICATIONS

IF / Tuner	
1. Input Frequency	950 MHz to 2150 MHz
2. Input Signal Level	-25 to -65dBm
3. Input Impedance	75 ohm nominal
4. Input Connector	F-type, IEC 109-24, Female
5. FEC Decoder	Convolutional Code Rate 1/2, 2/3, 3/4, 5/6 and 7/8 with Constraint Length K=7
6. Demodulation	QPSK
7. Symbol rate	2-45 Ms/s
8. IF Frequency / Bandwidth	480MHz / 30MHz Type
9. LNB Power & Polarization	V13 / H18, 450mA Max, over current protection
10. DiSEqC Control	Ver. 1.0 / 1.2 Compatible
Audio / Video Decoding	
1. Video Decoder	MPEG-2 MP@ML (ISO/IEC 13818-2)
2. Input Rate	60Mbit/s Max
3. Video Resolution	720 x 480(NTSC), 720 x 576 (PAL)
4. Aspect Ratio	4:3, 16:9
5. Audio Decoder	MPEG-1 (ISO/IEC 11172-3)
6. Audio Mode	Mono L/R, Stereo
7. Audio Sampling Frequency	32, 44.1, 48 KHz
Audio / Video Output	
1. SCART	TV / VCR
Serial Data Interface	
1. Connector Type	Mini USB Type
2. Signal	RS-232C, Max. 115200Bps
Power Supply	
1. Supply Voltage	110 ~ 240V
2. Power Consumption	Max.25W
General	
1. Weight	Approx. 0.83 Kg
2. Dimensions	83(W) x 173(D) x 32(H) mm